

Mystik[®] JT-4[®] Synthetic 4-Cycle All-Terrain Vehicle Motor Oils

OVERVIEW




- Premium synthetic base oils, combined with a special additive system designed for all-terrain vehicle (ATV) and utility vehicle (UTV) engines, provide outstanding protection.
- Full-synthetic formulas provide optimum high- and low-temperature performance, minimize volatility, enhance fuel economy, and improve cold-temperature performance and high-temperature thermal and oxidation stability.

FEATURES & BENEFITS



- Superior protection against engine wear, rust, and corrosion, ensuring engine cleanliness and promoting longer engine life.
- Extra protection for gasoline-powered ATV and UTV engines requiring a JASO MA quality oil.
- Protect in extreme hot and cold temperatures, with excellent thermal and oxidation stability.
- Permit lubrication flow during cold weather start-up.
- Maintain equipment performance and reliability.
- Excellent rust protection for wet riding environments.

APPLICATIONS



- For use in 4-cycle, gasoline-powered ATV and UTV engines, including those manufactured by Arctic Cat, Bombardier, Honda, Kawasaki, Polaris (including 1000 ProStar), Yamaha, and other original equipment manufacturers.
- Recommended for use in 4-cycle gasoline powered ATV and UTV engine applications requiring a JASO MA quality oil.
- Designed to be used in wet clutch applications that require JASO MA quality oil.
- Ideal for high-performance engines operating in extreme low and high temperatures and where performance demands the most from your oil.
- Select the SAE 0W-40 grade if frequent usage at low temperatures is expected.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for Mystik JT-4 Synthetic 4-Cycle All-Terrain Vehicle Motor Oils:**

Material Code	663079002	663080002
SAE Grade	0W-40	10W-40
Gravity, ASTM D237, °API	33.8	31.9
Density, lb/gal	7.13	7.21
Flash Point, ASTM D92, COC, °F (°C)	428 (220)	453 (234)
Pour Point, ASTM D97, °F (°C)	-56 (-51)	-22 (-30)
Viscosity, ASTM D445		
cSt at 40°C	93	98.4
cSt at 100°C	14.8	14.9
Viscosity Index, ASTM D2270	166	158
CCS Viscosity, cP (°C), ASTM D5293	6000 (-35)	5660 (-25)
NOACK Volatility, ASTM D5800, % Loss	7.0	9.0
Color, ASTM D1500	2.5	2.5
Sulfated Ash, ASTM D874, m%	0.9	1.0
TBN, ASTM D2896, mg KOH/g	9.5	9.2

Mystik and JT-4 are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.